

New Holland Rotavators

The perfect partner of your farms



New Holland Rotavators Features:

- ❖ 4-speed gear box – suitable for all types of soil
- ❖ More Blades – for better pulverisation
- ❖ Special Duo-cone waterproof seal – for longer life and suitable for puddling
- ❖ Better efficiency and less diesel consumption
- ❖ More warranty (one year)



Technical Specifications

Model	RE 125 (4 Feet)	RE 165 (5 Feet)	RE 185 (6 Feet)	RE 205 (7 Feet)
Total Width (mm)	1360	1760	1960	2160
Working Width (mm)	1250	1650	1850	2050
Weight (kg)	290	385	408	437
No of Flanges	7	9	10	11
No of Blades	36	48	54	60
Tractor HP required	30-40	40-45	45-50	>50
Rotavator Height (mm)	1025			
Blade Type	Square L & C Type			
Blade Thickness (mm)	7			
Distance between flanges (mm)	180			
Rotor Diameter (mm)	76.1			
Drive System	Multi-speed heavy-duty transmission gear drive			



Available Rotor RPM@540 PTO RPM

GEAR A (INPUT SHAFT)	GEAR B (OUTPUT SHAFT)	ROTOR RPM
16	20	172
17	19	193
19	17	241
20	16	269



High Quality PTO Shaft with shear bolt-added safety



Side Geared Transmission: Positive drive
-No shock load on tractor



Multi-speed gearbox-4 speed options



Hi-Quality Blades
-Longer Life & Better Pulverisation



Rotor hub with heavy duty/High oil capacity cover-Durability



Long Life taper roller bearing-Durability



Special duo-cone water proof double sealing system-Puddling suitability

*New Holland reserves the right to change the specifications of its products without prior notice.

* Tractor HP requirement varies with soil type/condition and moisture percentage.

Authorised Dealer

New Holland Fiat (India) Pvt. Ltd.

Plot No. 03, Udyog Kendra, Greater Noida, District Gautam Budh Nagar,
Uttar Pradesh. Tel.: +91 120 3056000 | Fax: +91 120 3056989 | www.newhollandindia.co.in
Toll Free No.: 1800 419 0124